




Výrobky pro rozvody studené, teplé vody a vytápění (standardní, I.)

Trubka S 5 / PN 10 / SDR 11


D mm	t mm	l mm	KÓD	[m]	kg/m
20	2,2	4000	STR020P10X	100	0,121
25	2,3	4000	STR025P10X	60	0,164
32	2,9	4000	STR032P10X	40	0,258
40	3,7	4000	STR040P10X	24	0,413
50	4,6	4000	STR050P10X	16	0,636
63	5,8	4000	STR063P10X	12	1,004
75	6,8	4000	STR075P10X	8	1,401
90	8,2	4000	STR090P10X	4	2,014
110	10,0	4000	STR110P10X	4	3,009
125	11,4	4000	STR125P10X	4	3,910


Trubka S 3,2 / PN 16 / SDR 7,4

D mm	t mm	l mm	KÓD	[m]	kg/m
16	2,2	4000	STR016P16X	160	0,094
20	2,8	4000	STR020P16X	100	0,145
25	3,5	4000	STR025P16X	60	0,227
32	4,4	4000	STR032P16X	40	0,367
40	5,5	4000	STR040P16X	24	0,566
50	6,9	4000	STR050P16X	16	0,886
63	8,6	4000	STR063P16X	12	1,387
75	10,3	4000	STR075P16X	8	1,990
90	12,3	4000	STR090P16X	4	2,839
110	15,1	4000	STR110P16X	4	4,274
125	17,1	4000	STR125P16X	4	5,530


Trubka S 2,5 / PN 20 / SDR 6

D mm	t mm	l mm	KÓD	[m]	kg/m
16	2,7	4000	STR016P20X	160	0,107
20	3,4	4000	STR020P20X	100	0,169
25	4,2	4000	STR025P20X	60	0,259
32	5,4	4000	STR032P20X	40	0,423
40	6,7	4000	STR040P20X	24	0,657
50	8,3	4000	STR050P20X	16	1,013
63	10,5	4000	STR063P20X	12	1,611
75	12,5	4000	STR075P20X	8	2,288
90	15,0	4000	STR090P20X	4	3,332
110	18,3	4000	STR110P20X	4	4,977
125	20,8	4000	STR125P20X	4	6,470


Trubka S 2,5 / PN 20 / SDR 6 – délka 3 m

D mm	t mm	l mm	KÓD	[m]	kg/m
20	3,4	3000	STR020P203	75	0,169
25	4,2	3000	STR025P203	45	0,259
32	5,4	3000	STR032P203	30	0,423

Všechny výše uvedené trubky lze po předchozím projednání vyrobit také v jiných délkách, než jsou uvedeny v katalogu.